



PROJECT _____

TYPE _____

NOTES _____

QUANTITY _____

DATE _____



Hexagonal ceiling suspended luminaire made from die-cast aluminium; surface Bronze; wet painted; brushed; inclusive adjustable cable suspension max. 4000mm in Signal Black; with COB (Chip on Board) technology for maximum efficiency; light colour 1800 K - 3000 K colour warm dimming; CRI \geq 90; 24 V; degree of protection IP20; Class 3; driver included; ceiling base included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

GENERAL

Ceiling _____

Suspended _____

Bronze _____

IP20 _____

Interior _____

570 lm _____

LED

colour warm dimming _____

1800 K - 3000 K _____

CRI \geq 90 _____

initial MacAdam \leq 2 SDCM _____

OPTICAL

Standard _____

beam angle 36° _____

ELECTRICAL

excl. power supply _____

24 V _____

system 7.0 W _____

Class 3 _____


PHYSICAL

length 77 mm _____

width 77 mm _____

height 300 mm _____

0.82 kg _____



[‘22646LQ9’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.