



PROJECT _____

TYPE _____

NOTES _____

QUANTITY _____

DATE _____



GENERAL

Ceiling _____
 Suspended _____
 Black Matt + White Opal Glass _____
 IP20 _____
 Interior _____
 260 lm _____
 CIE flux code: 26 51 76 60 87 _____

LED

lamp QT14 _____
 socket G9 _____
 max. per socket 5.0 W _____
 3000 K _____
 CRI ≥ 80 _____
 initial MacAdam ≤ 6 SDCM _____

ELECTRICAL


220 - 240 V _____
 inset 3.0 W _____
 Class 1 _____

PHYSICAL

diameter 125 mm _____
 height 135 mm _____
 0.5 kg _____
 cable length incl. 2.5 m _____
 suspension mm _____



Ceiling suspended luminaire; italian hand blown white opal glass; mounting made from aluminium in Black Matt; powder coated; matt texture; inclusive adjustable cable suspension max. 2500mm; lamp socket G9; lamp type QT14; max. 5W; 220 - 240 V; degree of protection IP20; Class 1; lamp not included;



[‘2521GOWB0’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.

2521G0WB0



LAMPS

QT14 LED Lamp

Type	Ø·H (MM)	Item number
2700K G9	15-52	9010G802
3000K G9	18-49	9010G804
3000K G9	17-54	9019G703