




**PROJECT** \_\_\_\_\_

**TYPE** \_\_\_\_\_

**NOTES** \_\_\_\_\_

**QUANTITY** \_\_\_\_\_

**DATE** \_\_\_\_\_



Free standing luminaire made from aluminium; surface Black Matt; powder coated; matt texture; RAL 9005; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; CRI ≥ 90; beam angle 30°; spotlight head 360° rotatable and 145° tiltable; degree of protection IP20; Class 3; cable plug with dimmer switch; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

**GENERAL**

Floor \_\_\_\_\_

Surface \_\_\_\_\_

tilt max 145 ° \_\_\_\_\_

rotation 360 ° \_\_\_\_\_

Black Matt \_\_\_\_\_

RAL 9005 <sup>a</sup> \_\_\_\_\_

IP20 \_\_\_\_\_

Interior \_\_\_\_\_

CIE flux code: 97 100 100 100 \_\_\_\_\_

100 \_\_\_\_\_

**LED**

2700 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

initial MacAdam ≤ 3 SDCM \_\_\_\_\_

**OPTICAL**

Standard \_\_\_\_\_

beam angle 30° \_\_\_\_\_

**ELECTRICAL**

dimmable \_\_\_\_\_

220 - 240 V \_\_\_\_\_

system 8.0 W \_\_\_\_\_

Class 3 \_\_\_\_\_

**PHYSICAL**


diameter 27 mm \_\_\_\_\_

height 127 mm \_\_\_\_\_

2.83 kg \_\_\_\_\_

cable plug with dimmer switch \_\_\_\_\_

<sup>a</sup> Colour may deviate slightly due to production conditions.



[‘477154B3’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.