



PROJECT _____

TYPE _____

NOTES _____

QUANTITY _____

DATE _____



GENERAL

Floor _____
 Recessed _____
 Inox _____
 IP67 _____
 IK08 _____
 Exterior _____
 CIE flux code: 25 48 71 0 100 _____

LED

3000 K _____
 CRI ≥ 90 _____
 L70 / 55000h _____
 initial MacAdam ≤ 3 SDCM _____

OPTICAL

Wide _____
 beam angle 43° _____
 UGR < 10 _____
 ≥65° < 1500 cd/m² _____

ELECTRICAL

phase-cut dim _____
 220 - 240 V _____
 system 5.0 W _____
 Class 2 _____


PHYSICAL

diameter 55 mm _____
 height 95 mm _____
 0.38 kg _____


CUTOUT

recessed depth 100 mm _____

LIGHT DISTRIBUTION



Round floor recessed luminaire made from stainless steel and glass; surface Inox; recessed depth 100 mm; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; beam angle 43°; degree of protection IP67; Class 2; driver not included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;





MOUNTING ACCESSORIES

Ground Housing

Type

MAP 0.6 | CHART 0.6 | BLINK TRIM | TRIMLESS

Ø-H (MM)

132.105

Item number

90012201