




PROJECT _____

TYPE _____


NOTES _____

QUANTITY _____

DATE _____



Floor surface mounted luminaire made from die-cast aluminium; surface Bronze; powder coated; matt texture; PCB 3-step binning; phase-cut dim; light colour 3000 K; CRI ≥ 80; 220 - 240 V; degree of protection IP65; Class 1; fixation base not included; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;



GENERAL

Floor _____
 Surface _____
 Bronze _____
 IP65 _____
 Exterior _____
 610 lm _____
 CIE flux code: 68 95 100 100 _____
 100 _____

LED

3000 K _____
 CRI ≥ 80 _____
 L80 / 50000h _____
 initial MacAdam ≤ 3 SDCM _____

OPTICAL

Asymmetric _____


ELECTRICAL

phase-cut dim _____
 220 - 240 V _____
 system 11.4 W _____
 Class 1 _____

PHYSICAL

diameter 80 mm _____
 height 28 mm _____
 0.38 kg _____

LIGHT DISTRIBUTION



[7582A4Q4] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.

**BASE****Pole 250**

Type	Colour	Ø-H (MM)	Item number
GATE 2.0	Anthracite Grey	80-250	910124A0
GATE 2.0	Bronze	80-250	910124Q0

Pole 450

Type	Colour	Ø-H (MM)	Item number
GATE 2.0	Anthracite Grey	80-450	910125A0
GATE 2.0	Bronze	80-450	910125Q0

Pole 650

Type	Colour	Ø-H (MM)	Item number
GATE 2.0	Anthracite Grey	80-650	910126A0
GATE 2.0	Bronze	80-650	910126Q0